

Air Curtain

The air curtain adopts cross flow blower to generate high speed air flow downward, that be installed upward side of the entrance door or window, to isolate the indoor air from the outdoor air and reduce the loss of indoor cool air, also prevent the insects and dust from entering the indoor environment.



Washable filter



Quiet function



Compact design



Easier maintainability

- Optimized cross-flow fan and good performance motor are adopted.
- Micro processor controlling with high reliability and long service life.
- Anti-corrosion thanks to two-side painted electro-galvanized metal case.
- High quality galvanized steel casing with double-sided plastic spray processing, high anti-corrosion.
- Good strength structure provides powerful airflow.
- Integrated electric components, easy maintenance.
- High performance cross flow fan blade with 3D-optimized streamlined.



Nominal test condition(temperature)		
Item	DB(C)	WB(C)
Cooling	27	19.5
Heating	21	-

Model			FM-1.25-9-K	FM-1.25-12-K
Power supply	V/Hz		220-230/50	220-230/50
Power input	W		110	140
Air flow volume	m ³ /h		1200	1650
Sound pressure level (H/L)	dB (A)		59	61
Dimension (W×D×H)	Outline	mm	900x215x193	1200x215x193
	Package	mm	1015x270x256	1315x270x256
Net weight /gross weight	kg		16/18	20/22
Loading quantity	40'GP	set	848	660
	40'HQ	set	954	746
Setting height	m		2.3-3	2.3-3
Standard	Wired remote controller		ZY611	ZY611

Note:Gree reserves the right to modify the specifications without prior notice. Please confirm the final specifications with sales representatives.